

Go2Tile Carpet Tile Specifications

MY FLOORS (NZ) LTD SPECIFICATIONS

+Go2Tile™ CARPET TILES

OUR MOST TRUSTED MODULAR FLOORING SOLUTION

| | | | |
|----------------------|---|----------------|--------------------------------------|
| Construction | Multi-level loop | Pile Height | 2.5 - 6.0mm (±0.5mm) |
| Yarn | Invista Nylon 6 | Backing | EuroBac or fibreglass Reinforced |
| Colour System | 100% Solution Dyed | Tile Size | 500 x 500 mm (5m2/box) |
| Gauge | 1/12 | Total Height | 6 - 8mm (±1.5mm) |
| Stitches | 10 per inch | Flammability | Passed (GB 8624-2006) |
| Pile Weight | 21 oz/yd2 | Static Control | Life-of-the-carpet Static Protection |
| Recommended Adhesive | Specially formulated Project Floors ProjectStik | Area of Use | Heavy Commercial |

REACTION-TO-FIRE PERFORMANCE COMPLIANCE

| AREA OF BUILDING | MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010 | | |
|--|---|---|-------------------|
| | Buildings not protected with an automatic fire sprinkler system | Buildings protected with an automatic fire sprinkler system | Go2Tile complies? |
| Sleeping areas and exitways in buildings where care or detention is provided | 4.5 kW/m2 | 2.2 kW/m2 | ✓ 5.0 kW/m2 |
| Exitways in all other buildings | 2.2 kW/m2 | 2.2 kW/m2 | ✓ 5.0 kW/m2 |
| Firecells accommodating more than 50 persons | 2.2 kW/m2 | 1.2 kW/m2 | ✓ 5.0 kW/m2 |
| Exitways in all other buildings | 1.2 kW/m2 | 1.2 kW/m2 | ✓ 5.0 kW/m2 |

Go2Tile Carpet Tile Specifications

MY FLOOR (NZ) LTD SPECIFICATIONS



GREAT BARRIER 03



GREAT BARRIER 05



GREAT BARRIER 06



GREAT BARRIER 07



GREAT BARRIER 15



BLANKET BAY

APPROVED INSTALLATION METHODS

