



HOME HEAVY DUTY RESIDENTIAL
OR LIGHT COMMERCIAL
LUXURY VINYL WOODPLANK

SPECIFICATIONS	
Number of Colours	13
Packaging per box	3.37m ²
Plank Dimensions	1219 x 184mm
Performance Classification EN 685	21-23, 31
Total thickness EN 428	2.0mm
Wear layer thickness EN 429	0.33mm
Surface Treatment	Yes/PU
Beveled PU Edges	Yes
Residual indentation EN 433	0.05mm
Caster chair suitability EN 425	Suitable for castor chairs in accordance with DIN 68131 Type W
Behaviour to fire DIN 4102	BI
Impact sound improvement DIN 52210	$\Delta L_w=8$ dB
Colour fastness DIN 53389	> 6
Electrostatic characteristics DIN 51953	> 1010
Chemical resistance DIN 51958	Present
Slip resistance	R11
Adhesive recommendation	ProjectBond
Please refer to separate cleaning, maintenance and installation instructions	



HOME HEAVY DUTY RESIDENTIAL
OR LIGHT COMMERCIAL
LUXURY VINYL WOODPLANK

INSTALLATION GUIDE

PREPARATION:

Most solid substrates that are even clean and crack free, with a temperature of not less than 15°C are suitable. The relevant standards i.e. BS 8203:2001 must be complied with.

Where underfloor heating is installed the system must not exceed 28°C and it must be switched off for at least 48 hours prior to and following installation of the tiles.

Subfloor must be permanently dry, smooth, level, clean and free from loose materials of any kind. Moisture content to be no more than 15 - 20%.

Acclimatize flooring: Once onsite, remove tiles from their packaging and fan out like a deck of cards. Preferably for a minimum of 24 hours before laying, or as long as possible if time constraints exist.

INSTALLATION:

To create the best layout, rooms should be divided and marked to facilitate a balanced distribution of tiles. The room temperature should be at least 18 °C, the relative humidity max. 75 %. The flooring must be acclimatized in the room to be floored for at least 24 hours before being put down. Likewise this temperature must be maintained up to 72 hours after the floor has been laid.

My Floor floor coverings must be glued into place with a dispersion adhesive using the wet gluing method. My Floor Floor Stick Adhesive is recommended. Certain installation conditions (e.g. strong sunlight, high levels of moisture etc.) require specialist installation methods.

My Floor Easy Lay uses FloorStick Pressure Sensitive. Home and Work use FloorStick Vinyl Adhesive.

1. Work in small areas at a time.
2. Adhesive application: Use a 1mm "V" notched trowel to spread the adhesive. As a guide 1 litre of adhesive should cover approx 4-5m².
3. While the adhesive is still wet, drop the tiles into place. Bed them in place using hand pressure.
4. Immediately wipe off any excess adhesive with a damp cloth.
5. Once the adhesive has had a chance to tack up, roll the entire floor with a 30-40kg floor roller. Repeat after 90 minutes.

FINISH:

1. Vacuum, dust mop or damp mop to remove all loose dirt.
2. Apply polish (Platinum 25 / Satin) in a thin coat using a lint free mop and allow to dry thoroughly.
3. Subsequent coats should be applied at right angles to the previous one to ensure an even coverage.
4. Apply 2-3 coats total.

GENERAL INSTRUCTIONS:

Uniformity of color of the goods is only guaranteed for deliveries of one production batch. Slight deviations cannot however be excluded. Damaged or faulty tiles/planks must be separated out prior to laying and returned with a complaint indicating the article and batch number. Office stools that are to be used on My Floor products must be fitted with soft type W castors according to DIN 68131.

CLEANING AND MAINTENANCE GUIDE

INITIAL CLEAN AT HAND OVER

Vacuum, dust mop, or damp mop to remove all loose dirt. Remove all traces of glue left from the installation using a cleaner as advised by the adhesive manufacturer. If the floor is heavily soiled due to the construction process it should be scrubbed clean using an alkaline cleaner diluted in accordance with the manufacturer's instructions. The alkaline cleaner should be left on the floor for a few minutes to allow it to react with the dirt. A rotary scrubbing machine fitted with a clean appropriate scrubbing pad will help speed up this process in large areas. For small areas the alkaline cleaner can be mopped onto the floor. The dirty residue should be removed with a wet vacuum or mop and the floor should then be thoroughly rinsed and allowed to dry.

ONGOING MAINTENANCE

Vacuum, dust mop or damp mop the floor daily to remove loose dirt and dust. Marks should be removed by using a neutral cleaner.

For stubborn marks an alkaline cleaner can be used. Remember to leave the cleaner on the mark for a few minutes to allow it to take maximum effect.

In areas of medium to low traffic the floor should be simply dry buffed with a rotary machine fitted with a clean appropriate buffing pad.

In heavy traffic areas the floor should be regularly cleaned using a floor cleaner/scrubber, the frequency will depend on the traffic conditions of the area. The floor maintainer should be diluted in accordance with the manufacturer's instructions, and either mopped onto the floor and allowed to dry or applied in a spray and buffed dry using a rotary machine fitted with a clean appropriate pad.

APPLICATION OF A FLOOR POLISH OR DRESSING

My Floor products incorporate a polyurethane surface treatment, which means that in many situations it is not always necessary to apply a floor dressing. However, the application of a floor dressing will provide additional protection in heavily trafficked areas & is recommended to enhance the floorcovering.

A high-solids, metalised polish, a polymer dispersion such as Platinum 25, Satin or Uno will provide good protection for the floor. Before application, ensure that the floor is clean and free of any other finishes. It is recommended that the polish/dressing used is compatible with all other maintenance products.

The polish/dressing should be applied in a thin coat using a lint free mop and allowed to dry thoroughly. Subsequent coats should be applied at right angles to the previous one to ensure an even coverage. Two/three coats should be sufficient to provide good protection in heavily trafficked areas.

If a polish/dressing has been applied this will need to be removed from time to time. The interval for removal is usually 6 months but again this depends on traffic conditions. Essentially, the polish/ dressing should be removed when routine maintenance is starting to become less effective.

To remove the polish/dressing first ensure that the floor is clean of all dust and dirt. Then apply the stripper recommended by the polish/dressing manufacturer and leave it on the floor for a few minutes to break down the polish/dressing. The floor should then be scrubbed using a rotary scrubbing machine fitted with a clean appropriate scrubbing pad. The resulting residue should be removed with a wet vacuum or mop and the floor should be rinsed clean with clean water. When dry the polish/dressing can be re-applied.

TIPS TO ENSURE SUCCESSFUL MAINTENANCE OF MY FLOOR PRODUCTS.

An effective dirt barrier system at entrances will significantly aid your maintenance programme. The dirt barrier should be at least 3 paces deep and be effective for both dry and wet soiling.

A regular programme of maintenance is always the most effective - Prevention is Better than Cure.

Always use clean equipment; equipment should be cleaned after use.

Remove all spills straight away. Always follow the manufacturer's dilution rates and don't mix products from more than one manufacturer.

Protect the floor from dark rubber (car tyres, rubber mats etc) this will discolour the floor.

Do not allow furniture polish and other silicone cleaners to get onto the floor; these will cause a slip hazard.

Use protective pads under furniture legs and use polyurethane castors on heavy movable furniture.